


Brad® AUTOMATION > INDUSTRIAL IO DESIGNER GUIDE

European Core Program





TOTAL SYSTEM SOLUTION >

Molex® is a leading one-source supplier of interconnect products. Our team of highly skilled experts is focused on the design, development and distribution of innovative product solutions that touch virtually every walk of life. The Molex® product portfolio is among the world's most extensive, with over 100,000 reliable products. Because our product line includes automation products for passive media, network media and power applications, Molex® can interconnect an entire automation infrastructure—one total system solution from a global company dedicated to meeting your total system needs. Molex® utilizes extensive worldwide resources to meet customer needs on a local, regional and global level. Molex® offers well-established sales, product development, manufacturing and logistics resources in Asia, Europe and the Americas.

The products you need... when and where you need them.

The Brad® Core Program

- Molex® supports one of **the largest portfolios of connectivity and wiring solutions** in the industrial market for automotive manufacturing, automated machine tools, food and beverage, material handling and packaging, commercial vehicles and solar applications.
- The core program is part of this portfolio that is **focused on the standard requirements** related to automation in the European market and highlights the active and passive IO modules and the related connectivity products for installation in harsh environments.
- Molex® commits to timely availability of all parts listed here in this core program and can propose dedicated delivery process to adapt the timings or the package of the solution chosen by our customers.
- Molex® commits to **supporting its customers** by helping them choose the right network as well as the most optimized infrastructure solution for their application. The Molex® tech support team also supports its customers in selecting corresponding parts from the complete portfolio or designing customer-dedicated solutions and prototyping.
- Beyond all part numbers available in this catalog dedicated to the standard IO interconnectivity, Molex® offers a high customizability of all parts (length, labeling, further connector variations...) as well as a huge range of complementary products that would cover all aspects of the automation infrastructures.

Molex® has the right solution for your automation application!

Find the Latest Innovations and Information at **Molex.com**

For the most in-depth and up-to-date information on all our products, visit Molex.com. It's designed to help you get more done in less time with advanced search capabilities, 3D models, product specifications, easy sample ordering and more.



» MOLEX.COM

Molex.com provides a first stop for comprehensive overviews of our industrial products. Some of the tools you'll find are:

Capabilities Videos

Short online videos highlight key industry products, as well as our unique cross-functional design and manufacturing capabilities.

Featured Products

To find out about new products that can take your design to the next level, look no further than this convenient product spotlight.

Other Time-Saving Site Features

Monthly E-nouncements

Electronic newsletter keeps you up-to-date on our latest innovations

Favorite Products Feature

Lets you select and save up to 200 products as you browse

Electrical Testing Models and Data

Available on an array of products in our "Signal Integrity" section

New Videos, Webinars, Articles and More

Available right from our home page

Detailed Application Pages

Instant Access to Product Specs

TABLE OF CONTENTS

NETWORK ARCHITECTURE

Ethernet and 7/8" Power Distribution06

PROFIBUS and M12 Power Distribution07

DeviceNet and CC-Link08

M12/M8 Sensor Actuator Interconnection.....09

ETHERNET

PROFINET HarshIO Modules12-13

Ethernet/IP HarshIO Modules14-15

Modbus TCP HarshIO Modules16

Harsh-Duty Ethernet Switches17

PROFINET Infrastructure Components18

Ethernet/IP Infrastructure Components19

Ethernet Infrastructure Accessories.....20

PROFIBUS

PROFIBUS HarshIO Modules22-23

PROFIBUS Infrastructure Components24-25

POWER

Mini-Change® 7/8" Auxiliary Power Infrastructure Components26-27

Micro-Change® M12 Auxiliary Power Infrastructure Components28-29

PASSIVE MEDIA


MPIS® Distribution Boxes30-31

Micro-Change® M12 Connectivity32-37

Nano-Change® M8 Connectivity38-41

mPm® DIN Valve Connectors42-43


Complete Solution For Automation Infrastructures In Harsh Environments



All trademarks used herein are the property of their respective owners. Reference to any non-Molex trademarks is not intended to claim any endorsement or association between Molex and the respective trademark owners, and should not be construed.


IP67 rated digital IO modules for harsh environments are designed for direct machine mount applications.

Ethernet and 7/8" Power Distribution Architecture



Ethernet in combination with the industrial protocols like PROFINET or EtherNet/IP provide deterministic behavior for machine and process control applications with only COTS components.

The transition from the fieldbus to the Ethernet communication technologies helps to simplify the industrial infrastructures and enhance the management and maintenance of the devices providing a significant cost saving and performance improvement.



Type of Network

Multi station network
CSMA/CD – Carrier Sense Multiple Access with Collision Detection

Physical Media

Shielded 2 or 4 twisted pairs, AWG22 (PROFINET)
RJ45 or M12 D-Code Connectivity

Network topology

Point to point communication
Star topology with switches
Daisy chain through device integrated 3 ports switches
Ring and redundancy topology protocol dedicated functionalities


Maximum distance

100m between two devices
4 interconnection between 2 devices allowed
No termination required

Power and Communication

Power is supplied separately from network communication

PROFIBUS and M12 Power Distribution Architecture



PROFIBUS-DP (Decentralized Periphery) is a device level bus that supports both analog and discrete signals. It permits Mono-master or Multi-master systems, which provides a high degree of flexibility during system configurations.

PROFIBUS allows all automation devices, sensors, actuators, PLC's, etc. to communicate at speeds from 9.6 Kbps to 12 Mbps over distances from 100 to 1,200 meters.

Type of Network

Serial Device Bus – RS485
Cyclic master-slave communication (uses token passing sequence)

Physical Media

Shielded twisted pair, AWG 22.
D-Sub9, M12 B-Code connectivity

Network topology

Bus Topology, no drop line allowed

Maximum Devices

Max. 32 Stations per PROFIBUS segment that can be extended with repeaters to 126 Stations on one bus (maximum of 244 Bytes input and output possible for each slave)

Maximum distance

93.75Kbps and less – 1200 meters
500Kbps – 400 meters
1.5Mbps – 200 meters
12Mbps – 100 meters

Power and Communication


Power is supplied separately from communications bus.

Communication Methods


Peer-to-peer, multicast or cyclic master-slave (uses token passing sequence).

Termination

Terminating resistor on both ends of a segment via the D-Sub integrated resistor or the M12 terminating resistor.





DeviceNet and CC-Link Architecture Solutions




**Molex also provides
infrastructure solutions
for the support of DeviceNet
and CC-Link protocols.**

**For more information please
visit www.Molex.com**

M12 Sensor Actuator Interconnection



M8 Sensor Actuator Interconnection





Ethernet IO reliable connections in harsh environments.



Worldwide Unique Feature: Quicker Setups and More Uptime through Secure Connections Using the Brad® Ultra-Lock® Patented Connection System

- One simple push delivers a secure, consistent seal each and every time
- Eliminates connector-related intermittent signals that lead to costly production downtime
- Quick change-overs can now be a reality

React to Problems Sooner Using Easy-to-Read Diagnostics

- Visible LEDs provide maintenance personnel with ability to easily determine I/O, module and network status
- Scrolling 4-character display for IP addressing and module status
- Built-in web server for remote monitoring, configuration and diagnostics

Reduce Infrastructure Costs with Built-in 2-Port Ethernet Switch

- 10/100 Mbps auto-sensing
- Supports straight or crossover Ethernet cable

Reduce Inventory Costs Using Configurable I/O

- User configurable – 16 points of digital I/O can be set as either an Input or Output (also available in fixed I/O configurations)

Save Time Configuring or Replacing I/O Modules


- On PROFINET or EtherNet/IP, configuration setup can be downloaded on the HarshIO directly from the Master, IO-Controller or Scanner
- With simple-to-use push buttons, quickly adjust the last three octets of the IP address

Save Energy by Minimizing Power Supply

- On PROFINET, HarshIO supports PROFlenergy service, allowing the IO-Controller to minimize power supply to the connected HarshIO Module(s)

Brad® HarshIO Modules

Built-in Web Server with Password Protection




Push Buttons

Two push buttons located above the display window are used to:

1. Quickly adjust the last octet or last 3 characters of the module's IP address

2. Scroll through and view the Ethernet configuration mode





Extended characteristics and resistance

The Weld-Slag and Oil-Resistant (WSOR) cable delivers high flex and torsion performance and supports a wide range of temperatures (from -40°C to 90°C). Certified FT1 flame retardant, UV, Hydrolysis and Tear resistant, this cable would withstand the most severe conditions.

One solution for various applications

The cable is designed for use in multiple harsh-environment applications, in the automotive and robotic area, from welding to cutting-oil environments, conveying and most machine applications and can be terminated to a variety of industry-standard connectors.

Optimized and cost effective connectivity solution

As manufacturer of this cable range, Molex can control every step and cost of the production to provide price effective cordsets. Choosing this polyvalent WSOR cable helps also to reduce inventory costs. The WSOR cable can also be purchased raw by Molex for the termination on site.

Large range of cable qualities

This designer guide focus on cordsets with the WSOR cable quality. Molex provides additional cable standards to cover further market requirements. All standards have UL/CSA omologation.

Cable	PVC	WSOR	PUR
0,34mm ²	E03	B30	H09
0,25mm ²	E02	B41	H08
1,5mm ²		B35	B21
PROFINET		12	11

PVC

Very cost effective cable
Less demanding environment
Good water resistance
Ideal for conveying, packaging application

WSOR

Cost optimized cable
Wide application range
Oil and weld slag resistance
Ideal for automotive, robotic and machining application

PUR

High End range
Low Smoke Zero halogen
Good oil resistance
Ideal for public transport and mining application

Brad® Weld Slag & Oil Resistant Cable



WSOR cable spool

The WSOR cable is available from Molex as raw cable spool in 100m or 200m version. The order number can be found in each section.

On request the cable can also be ordered in 5km bulk.



Knurled/Hex Nut for WSOR cordsets

All WSOR M12 and M8 cordsets have a knurled/hex coupling nut to use with dynamometric torque tools to make sure that your connection is perfectly tight.



M8 Torque tool (wrench size 9)

Engineering No.	Standard Order No.
—	1203035017

M12 Torque tool (wrench size 13)

Engineering No.	Standard Order No.
—	1203035018

IP67 rated digital IO modules for harsh environments are designed for direct machine mount applications with PROFINET IO communication capabilities.

Specifications



PROFINET IO-Device, Conformance class B
 IP addressing: DCP or static
 Real-Time I/O update, up to 1 ms
 Services: PROFIenergy, SNMP V1/V2/V3, LLDP Send/Rec, MRP, I&M, Easy Device replacement, Fast Start-Up (FSU) < 500ms
 GSDML configuration file (downloadable via integrated Web server)
 Embedded display for diagnostic
 Grounding isolation between Input/logic and Output Power(1)
 Operating Temperature: -25 to 70°C
 Storage Temperature: -40 to +90°C
 Approvals: CE, UL, cUL, Rohs, REACH, PNO Certified

Brad® PROFINET HarshIO Modules




Brad® HarshIO IP67 PROFINET Modules

User manual and GSDML files to download under:

www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)

Ordering Information

Brad® HarshIO IP67 PROFINET Module 60mm M12



Connectivity

Ethernet:

2x Female M12 4P
 D-code
 Built-in 2 port
 switch Ultra-Lock®
 compatible

Inputs/Outputs:

8x Female M12
 5P A-code Dual
 IO signal per port
 Inputs 24V max.
 140mA Outputs
 24V max. 2A Ultra-
 Lock® compatible

Power:

1x Male 7/8"
 4 or 5 Pole
 1x Fem. 7/8"
 4 or 5 Pole
 Voltage: 24V Input
 8 Amps

Power Type	Input/Output (PNP)	Engineering No.	Standard Order No.
7/8" 5 Pole	16I	TCDEP-8D0P-D1U-G	112095-5048
	8I/8O	TCDEP-888P-D1U-G	112095-5050
	12I/4O	TCDEP-8B4P-D1U-G	112095-5051
	16O	TCDEP-80DP-D1U-G	112095-5049
	User Config.	TCDEP-8YYX-D1U	112095-5037
7/8" 4 Pole ⁽²⁾	16I	TCDEP-8D0P-DYU-G	112095-5052
	8I/8O	TCDEP-888P-DYU-G	112095-5053
	12I/4O	TCDEP-8B4P-DYU-G	112095-5054
	16O	TCDEP-80DP-DYU-G	112095-5055

(1) Not available on User Configurable IO model
 (2) 4 Poles Mini-Change® (7/8") cordsets are not listed in this brochure. For more information consult our web page or industrial automation catalog.

The compact 30mm wide version is designed to be installed in narrow areas, and is perfect for packaging and pick-and-place applications. The lower port count of this model provides a cost-effective module.

Specifications



PROFINET IO-Device, Conformance class B
 IP addressing: DCP or static
 Real-Time I/O update, up to 1 ms
 Services: SNMP V1/V2/V3, LLDP Send/Rec, I&M, Easy Device replacement,
 Fast Start-Up (FSU) < 500ms
 Grounding isolation (1) between Input/logic and Output Power
 Operating Temperature: -25 to 70°C
 Storage Temperature: -40 to +90°C
 Approvals: CE, UL, cUL, Rohs, REACH, PNO Certified

User manual and GSDML files to download under:


www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)

Brad® PROFINET HarshIO Modules



Brad® HarshIO IP67 PROFINET Modules

Brad® HarshIO IP67 PROFINET Module – 30mm M8



Power Type	Input/Output (PNP)	Engineering No.	Standard Order No.
M12 5 Pole	8I	TBDEP-880P-D84-G	112095-5064
	4I/4O	TBDEP-844P-D84-G	112095-5065
	8O	TBDEP-808P-D84-G	112095-5066
	User Config.	TBDEP-8YYP-D84	112095-5067

Connectivity

Ethernet:

2x Female M12 4P
 D-Code
 Built-in 2 port switch
 Ultra-Lock® compatible


Inputs/Outputs:

8x Female M8 3
 Poles Single IO
 signal per port
 Inputs 24V max.
 140mA Outputs 24V
 max. 1,4A

Power:

1x Male M12 5 Pole
 A-Code
 Voltage: 24V Input
 & Output, max. 4
 Amps

Brad® HarshIO IP67 PROFINET Module – 30mm M12



Power Type	Input/Output (PNP)	Engineering No.	Standard Order No.
M12 5 Pole	8I	TBDEP-480P-D8U-G	112095-5076
	4I/4O	TBDEP-440P-D8U-G	112095-5077
	8O	TBDEP-408P-D8U-G	112095-5078
	User Config.	TBDEP-4YYP-D8U	112095-5079

(1) Not available on User Configurable IO models.

Connectivity

Ethernet:

2x Female M12 4P
 D-Code
 Built-in 2 port switch
 Ultra-Lock® compatible

Inputs/Outputs:

4x Female M12
 5P A-Code Dual IO
 signal per port
 Inputs 24V max.
 140mA
 Outputs 24Vmax. 1,4A
 Ultra-Lock compatible

Power:

1x Male M12 5 Pole
 A-Code
 Voltage: 24V Input
 & Output, max. 4
 Amps

IP67 rated digital IO modules for harsh environments are designed for direct machine mount applications with EtherNet/IP communication capabilities.

Specifications



EtherNet/IP Adapter
 IP address: DHCP, Static Address, and 0xF5/0xF6 objects
 Real-Time I/O update, up to 1 ms
 Services: Automatic Conflict Detection (ACD), QuickConnect
 < 500ms (QC Class A device)
 EDS configuration file (downloadable via CIP File Service)
 Embedded display for diagnostic
 Grounding isolation¹ between Input/logic and Output Power
 Operating Temperature: -25 to +70°C
 Storage Temperature: -40 to +90°C
 Approvals: CE, UL, cUL, Rohs, REACH, ODVA Certified

Brad® EtherNet/IP HarshIO Modules




Brad® HarshIO IP67 EtherNet/IP Modules
 60mm and 30mm

User manual and EDS files to download under:

www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)

Ordering Information

Brad® HarshIO IP67 EtherNet/IP Module – 60mm M12



Connectivity

Ethernet:	Inputs/Outputs:	Power:
2x Female M12 4P D-Code Built-in 2 port switch Ultra-Lock® compatible	8x Female M12 5P A-Code Dual IO signal per port Inputs 24V max. 140mA Outputs 24V max. 2A Ultra-Lock® compatible	1x Male 7/8" 4 or 5 Pole 1x Fem. 7/8" 4 or 5 Pole Voltage: 24V Input & Output, max. 8 Amps

Power Type	Input/Output (PNP)	Engineering No.	Standard Order No.
7/8" 5 Pole	16I	TCDEI-8D0P-D1U-G	112095-5060
	8I/8O	TCDEI-888P-D1U-G	112095-5061
	12I/4O	TCDEI-8B4P-D1U-G	112095-5063
	16O	TCDEI-80DP-D1U-G	112095-5062
	User Config.	TCDEI-8YYX-D1U	112095-5011
7/8" 4 Pole ⁽²⁾	16I	TCDEI-8D0P-DYU-G	112095-5040
	8I/8O	TCDEI-888P-DYU-G	112095-5041
	12I/4O	TCDEI-8B4P-DYU-G	112095-5043
	16O	TCDEI-80DP-DYU-G	112095-5042
	User Config.	TCDEI-8YYX-DYU	112095-5020

(1) Not available on User Configurable IO model.

(2) 4 Poles Mini-Change® (7/8") cordsets are not listed in this brochure.
 For more information consult our web page or industrial automation catalog.



Brad® HarshIO IP67 Modules for EtherNet/IP featuring CIP Safety technology deliver significant operational advantages of protection and versatility for industrial safety applications.

Brad® EtherNet/IP CIP Safety HarshIO Modules

Specifications



EtherNet/IP CIP Safety IO Adapter
For use in safety applications, up to SIL3 and PLe; Mission time > 20 years
Real-Time I/O update, up to 10 ms
Output Bipolar version: max. 2A per dual channel
Support ODVA CIP Safety I/O generic profiles
Services: Automatic Conflict Detection (ACD), DLR Client
EDS upload file (downloadable via CIP File Service)
Integrated Web server for diagnostics
IP address: DHCP, Static Address and EtherNet/IP 0xF5/0xF6 objects
Grounding isolation between Input/logic and Output Power
Easy commissioning thanks to Molex SNCT software and RA RSLogix™ 5000
Operating Temperature: -25 to +70°C
Storage Temperature: -40 to +90°C
Approvals: CE, UL, cUL, Rohs, REACH, TUV(2), ODVA Certified




Brad® HarshIO IP67 EtherNet/IP CIP Safety Modules

User manual and GSDML files to download under:

www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)

Ordering Information

Brad® HarshIO IP67 EtherNet/IP CIP Safety



Power Type	Input/Output (PNP)	Engineering No.	Standard Order No.
7/8" 5 Pole	12I/4O	TCDEC-8B4P-D1U-G	112095-5111
	12I/4O (Bipolar)	TCDEC-8B4B-D1U-G	112095-5112
7/8" 4 Pole ⁽¹⁾	12I/4O	TCDEC-8B4P-DYU-G	112095-5107
	12I/4O (Bipolar)	TCDEC-8B4B-DYU-G	112095-5108


(1) 4 Poles Mini-Change® (7/8") cordsets are not listed in this brochure. For more information consult our web page or industrial automation catalog.

Connectivity

Ethernet:
2x Female M12 4P D-code
Built-in 2 port switch Ultra-Lock® compatible

Inputs/Outputs:
8x Female M12 5P A-Code Dual IO signal per port
Inputs 24V max. 140mA
Outputs 24V max. 2A
Ultra-Lock® compatible

Power:
1x Male 7/8" 4 or 5 Pole
1x Fem. 7/8" 4 or 5 Pole
Voltage: 24V Input & Output, max. 8 Amps





IP67 rated digital IO modules for harsh environments are designed for direct machine mount applications with Modbus TCP communication capabilities.


Specifications

Modbus TCP server
Speed: 10/100 Mbps. (auto-negotiation, full duplex)
Data Access: I/O data
IP address: DHCP, Static Address
Embedded display for diagnostic
Operating Temperature: -25 to +70°C
Storage Temperature: -40 to +90°C
Approvals: CE, UL, cUL, Rohs, REACH, Schneider Certified

User manual to download under:
www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)

Ordering Information

Brad® HarshIO IP67 Modbus TCP/IP Module – 60mm M12



Connectivity

Ethernet: 2x Female M12 4P D-Code Built-in 2 port switch Ultra-Lock® compatible	Inputs/Outputs: 8x Female M12 5P A-Code Dual IO signal per port Inputs 24V max. 140mA Outputs 24V max. 2A Ultra- Lock® compatible	Power: 1x Male 7/8" 4 or 5 Pole 1x Fem. 7/8" 4 or 5 Pole Voltage: 24V Input & Output, max. 8 Amps
----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------

MODBUS
TCP



Brad® HarshIO IP67 Modbus TCP Module 60mm

Power Type	Input/ Output	Engineering No.	Standard Order No.
7/8" 5 Pole	User Config.	TCDEM-8YYX-D1U	112095-0009
7/8" 4 Pole ⁽¹⁾	User Config.	TCDEM-8YYX-DYU	112095-5038

(1) 4 Poles Mini-Change® (7/8") cordsets are not listed in this brochure. For more information consult our web page or industrial automation catalog.

IP67 rated fast Ethernet switches for harsh environments are designed for direct machine mount applications.

Specifications


Unmanaged IP67 switches
Speed 10/100Mbps auto negotiation, full or half duplex
Auto-learning with no software or configuration required
Operating Temperature: -40 to +75°C
Storage Temperature: -40 to +90°C
Approvals: CE, UL, cUL

Brad®
Harsh-Duty
Ethernet
Switches



Ordering Information

Brad® Harsh-Duty Unmanaged IP67 Ethernet Switch – 60mm M12



Connectivity


Ethernet:
8x Female M12 4P
D-Code
Ultra-Lock®
compatible

Power:
1x Male 7/8" or
1x Male M12
4 or 5 Pole
1x Fem. 7/8" or
1x Fem. M12
4 or 5 Pole
Dual power supply
entry, 9-36VDC

Brad® Harsh-Duty Ethernet switches — 60mm and 30mm

Power Type	Engineering No.	Standard Order No.
7/8" 5 Pole	DRL-780	112105-5002
7/8" 4 Pole	DRL-781	112105-5004
M12 5 Pole	DRL-782	112105-5006

Brad® Harsh-Duty Unmanaged IP67 Ethernet Switch – 30mm M12



Connectivity

Ethernet:
5x Female M12 4P
D-Code

Power:
1x Male M12 5 Pole
9-36VDC

Power Type	Engineering No.	Standard Order No.
M12 5 Pole	DRL-750	112111-5001

Plug & Play infrastructure to interconnect Ethernet IP67 devices based on D-Code M12 standard connectors.

**Brad®
PROFINET
Infrastructure
Components**

Ordering Information

Brad® PROFINET Single-Ended M12 Cordsets



PROFINET WSOR Cable 12				
	Male Straight		Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	E10A00612M020	130048-0313	E10A00712M020	130048-0312
5m	E10A00612M050	130048-0295	E10A00712M050	130048-0300
10m	E10A00612M100	130048-0296	E10A00712M100	130048-0301
20m	E10A00612M200	130048-0297	E10A00712M200	130048-0302
30m	E10A00612M300	130048-0298	—	—

Brad® PROFINET Double-Ended M12 Cordsets



PROFINET WSOR Cable 12				
	Male to Male Straight		Male to Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	E11A06012M010	120108-8304	E11A06312M010	120108-0508
2m	E11A06012M020	120108-8305	E11A06312M020	120108-0509
5m	E11A06012M050	120108-8308	E11A06312M050	120108-0510
10m	E11A06012M100	120108-8311	E11A06312M100	120108-0511
15m	E11A06012M150	120108-8313	—	—
20m	E11A06012M200	120108-8315	—	—
30m	E11A06012M300	120108-8317	—	—



PROFINET Cable 12 Specification*

Datasheet Part No: CAB-12

AWG22 Shielded PROFINET Cat5e cable

Conductors: 2x2x0,34mm²
(White, Yellow, Blue, Orange)

Jacket material: Green Blend PUR,
flame retardant, oil, UV & Weld Slag
resistant, silicone & FCKW free

Diameter: 6,7 +/-0,2mm

Static Operating Temp:
-40 to +80°C

Dynamic Operating Temp: -25 to
+85°C

Drag Chain (>5 Mio Cycles)
& torsion suitable

Approvals: UL, CSA

PROFINET Cable 12 100m Bulk cable

Engineering No.	Standard Order No.
CAB-12-100	112180-0077

This cable can also be used for any other
Ethernet communication protocol

ETHERNET
POWERLINK

**MODBUS
TCP**

EtherCAT

* Detailed cable specification attached to
bulk cable drawings

Brad® PROFINET M12 Receptacle



Female M12 Receptacle to RJ45

PNET RJ45 Adapters		
Length	Engineering No.	Standard Order No.
1m	ERWPAU7012M010	120108-0519
2m	ERWPAU7012M020	120108-0520



Male M12 Connector to RJ45

PNET RJ45 Adapters		
Length	Engineering No.	Standard Order No.
1m	E16A06012M010	120108-0521
2m	E16A06012M020	120108-0522
5m	E16A06012M050	120108-0523
10m	E16A06012M100	120108-0524

Ordering Information

Brad® EtherNet/IP Single-Ended M12 Cordsets



Brad®
EtherNet/IP
Infrastructure
Components

EtherNet/IP™



EtherNet/IP Cable Specification

Shielded Ethernet Cat5e cable


Conductors: 2 Pairs AWG26
(White/Green, Green, White/
Orange and Orange)

Jacket Material: Teal PVC

Operating Temperature:
-20°C to +75°C


Sun and Oil resistant

Approvals: UL, cUL, EtherNet/IP




Note:
Further technical information, datasheet or drawing
can be downloaded from the Molex® website using the
ordering part number.

Brad® EtherNet/IP Double-Ended M12 Cordsets




EtherNet/IP PVC Cable 15				
	Male to Male Straight		Male to Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	E11A06015M010	130048-0122	E11A06315M010	130048-0179
2m	E11A06015M020	130048-0124	E11A06315M020	130048-0181
5m	E11A06015M050	130048-0126	E11A06315M050	130048-0183
10m	E11A06015M100	130048-0128	E11A06315M100	130048-0185
15m	E11A06015M150	130048-0130	—	—
20m	E11A06015M200	130048-0010	—	—
30m	E11A06015M300	130048-0132	—	—

Brad® EtherNet/IP M12 Receptacle



Female Receptacle to RJ45

Ethernet RJ45 Adapters		
Length	Engineering No.	Standard Order No.
1m	ERWPAB3002M010	130058-0025
2m	ERWPAB3002M020	130054-0021




Male M12 Connector to RJ45

Ethernet RJ45 Adapters		
Length	Engineering No.	Standard Order No.
1m	E16A06015M010	130048-0280
2m	E16A06015M020	130048-8099
5m	E16A06015M050	130048-0237
10m	E16A06015M100	130048-8101



Ordering Information

Brad® Ethernet Bulkhead Adapter (M12 Female to RJ45)



Straight		90°	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
ER1PADAPTER	130054-0009	ER1PADAPTER90	130054-0010

Brad® Ethernet Field Attachable



M12 Male		M12 Female	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
E1AS06-52	130047-0018	E1AS00-52	130047-0017

Brad® RJ45 Connector



Engineering No.	Standard Order No.
85720-1050	85720-1050

Brad® Ethernet Infrastructure Accessories

EtherNet/IP™



“All trademarks used herein are the property of their respective owners. Reference to any non-Molex trademarks is not intended to claim any endorsement or association between Molex and the respective trademark owners, and should not be construed.”



IP67 rated digital IO modules for harsh environments are designed for direct machine mount applications.

Specifications

PROFIBUS DP-V0 Slave according EN 50170
Auto baud: all baud rates up to 12M Baud
Address Settings: 1 – 99 by 2 rotary switches
Operating Temperature: -25 to +70°C
Storage Temperature: -25 to +90°C
Approvals: CE, UL, PNO Certification




User manual and GSD files to download under:
www.molex.com (Select Automation & Industrial / Brad Automation / Support & Downloads)



Brad® HarshIO IP67 PROFIBUS Modules 60mm and 30mm

Ordering Information

Brad® HarshIO IP67 PROFIBUS Module – 60mm M12



Connectivity

PROFIBUS: 1x Male M12 5P B-Code 1x Fem. M12 5P B-Code	Inputs/Outputs: 8x Female M12 5P A-CodeDual IO signal per port Inputs 24V max. 140mA Outputs 24V max. 2A Ultra-Lock® compatible	Power: 1x Male 7/8" 5 Poles 1x Female 7/8" 5 Poles Voltage: 24V Input & Output, max. 8 Amps
--------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------

Power Type	Input/Output		Engineering No.	Standard Order No.
7/8" 5 Pole	NPN	16I	TCDPB-8D0N-B1U	112038-0030
		14I/2O	TCDPB-8C2N-B1U	112038-0028
		12I/4O	TCDPB-8B4N-B1U	112038-0026
		8I/8O	TCDPB-888N-B1U	112038-0024
	User Config.		TCDPB-8YYX-B1U	112038-5005
	PNP	16I	TCDPB-8D0P-B1U	112038-0031
		14I/2O	TCDPB-8C2P-B1U	112038-0029
		12I/4O	TCDPB-8B4P-B1U	112038-0027
		8I/8O	TCDPB-888P-B1U	112038-0025

All Brad® IP67 HarshIO Modules with Micro-Change® (M12) ports accept both threaded cordsets and the new Brad® Ultra-Lock® Connection System, the fastest, easiest and most secure connection ever.






Ultra-Lock® technology is designed for higher performance and reliability to eliminate downtime, increase productivity and lower costs.



The compact 30mm wide version is designed to be installed in narrow areas, and is perfect for packaging and pick-and-place applications. The lower port count of this model provides a cost-effective module.

Brad®
PROFIBUS
HarshIO Modules

Ordering Information
Brad® HarshIO IP67 PROFIBUS
Module – 30mm M8




Connectivity

PROFIBUS: 1x Male M12 5 Pole B-Code 1x Fem. M12 5 Pole B-Code	Inputs/Outputs: 8x Female M8 3 Poles Single IO signal per port Inputs 24V max. 140mA Outputs 24V max. 1,4A	Power: 1x Male M12 5 Pole A-Code Voltage: 24V Input & Output, max. 4 Ampere
----------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------

Power Type	Input/Output		Engineering No.	Standard Order No.
M12 5 Pole	NPN	8I	TBDPB-880N-B84	112038-0019
		6I/2O	TBDPB-862N-B84	112038-0017
		4I/4O	TBDPB-844N-B84	112038-0015
	PNP	8I	TBDPB-880P-B84	112038-0021
		6I/2O	TBDPB-862P-B84	112038-0018
		4I/4O	TBDPB-844P-B84	112038-0016
		8O	TBDPB-808P-B84	112038-0014

Brad® HarshIO IP67 PROFIBUS
Module – 30mm M12



Connectivity

PROFIBUS: 1x Male M12 5 Pole B-Code 1x Fem. M12 5 Pole B-Code	Inputs/Outputs: 4x Female M12 5P A-Code Dual IO signal per port Inputs 24V max. 140mA Outputs 24V max. 1,4A Ultra-Lock® compatible	Power: 1x Male M12 5 Pole A-Code Voltage: 24V Input & Output, max. 4 Ampere
----------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------

Power Type	Input/Output		Engineering No.	Standard Order No.
M12 5 Pole	NPN	8I	TBDPB-480N-B8U	112038-0009
		6I/2O	TBDPB-462N-B8U	112038-0007
		4I/4O	TBDPB-444N-B8U	112038-0005
	PNP	8I	TBDPB-480P-B8U	112038-0011
		6I/2O	TBDPB-462P-B8U	112038-0008
		4I/4O	TBDPB-444P-B8U	112038-0006
		8O	TBDPB-408P-B8U	112038-0003


Plug & Play PROFIBUS infrastructure to interconnect IP67 devices based on B-Code M12 standard connectors. Designed with PUR jacket material for better chemical and oil resistance, low-resistance contact design and 360° shielded head design to reduce RFI/EMI.

Ordering Information

Brad® PROFIBUS Single-Ended M12 Cordsets




PROFIBUS Shielded PUR Cable				
	Male Straight		Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	B05S06PP4M020	120098-0102	B05S07PP4M020	120098-0109
5m	B05S06PP4M050	120098-0104	B05S07PP4M050	120098-0111
10m	B05S06PP4M100	120098-0107	B05S07PP4M100	120098-0112
20m	B05S06PP4M200	120098-8053	B05S07PP4M200	120098-8054



PROFIBUS Shielded PUR Cable				
	Female Straight		Female 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	B05S00PP4M020	120098-0085	B05S01PP4M050	120098-0095
5m	B05S00PP4M050	120098-0087	B05S01PP4M100	120039-0136
10m	B05S00PP4M100	120098-0089	B05S01PP4M200	120098-8056
20m	B05S00PP4M200	120039-0122	B05S01PP4M300	120098-8057

Brad® PROFIBUS Double-Ended M12 Cordsets




PROFIBUS Shielded PUR Cable				
	Female to Male Straight		Female to Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	BB5S30PP4M010	120098-0006	BB5S33PP4M010	120098-0029
2m	BB5S30PP4M020	120098-0007	BB5S33PP4M020	120098-0031
5m	BB5S30PP4M050	120098-0010	BB5S33PP4M050	120098-0033
10m	BB5S30PP4M100	120098-0014	BB5S33PP4M100	120098-0035
15m	BB5S30PP4M150	120098-0160	BB5S33PP4M150	120098-8050
20m	BB5S30PP4M200	120098-0017	BB5S33PP4M200	120098-8051
30m	BB5S30PP4M300	120098-0019	BB5S33PP4M300	120098-8052

**Brad®
PROFIBUS
Infrastructure
Components**



PROFIBUS Cable Specification



PROFIBUS Twisted Pair
AWG22 (0,34mm²) cable

Conductors: 2x Red and Green

Jacket Material: Purple PUR

Voltage Rating: 300V


Operating Temperature:
-40 to +60°C

C-Track compatible (3M cycles)

Bend radius: 10x cable diameter

Approvals: UL, CSA

PROFIBUS M12 B-Code Connector Pinout (front view)



Ordering Information

Brad® PROFIBUS M12 Receptacles



PROFIBUS Shielded PUR Cable				
	Male		Female	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	BR5U76PP4M0203	120099-0015	BR5U70PP4M0203	120099-0007
4m	BR5U76PP4M0403	120099-0016	BR5U70PP4M0403	120099-0009

Brad® PROFIBUS M12 Field Attachables



Male		Female	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
BA5S06-32	120100-0002	BA5S00-32	120100-0001

Brad® PROFIBUS IP20 Bus Terminators




	With Diagnostic		Without Diagnostic	
Desc.	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
Straight	MA9D00-42	120103-5001	—	—
90°	PA9D01-42	120103-0001	PA9S01-42	120103-0005
45°	PA9D0B-42	120103-0003	—	—

Brad® PROFIBUS Accessories

PROFIBUS M12 Male Terminator	
Engineering No.	Standard Order No.
B05S06*	120102-0002*




PROFIBUS M12 Bus Tee	
Engineering No.	Standard Order No.
PDTS01*	120101-0002*




Brad® PROFIBUS Infrastructure Components




PROFIBUS Terminator Resistor Wiring




PROFIBUS Terminator Resistor Wiring



PROFIBUS Tee Wiring



PROFIBUS Max drop lengths






Plug & Play 5 Pole power distribution infrastructure to interconnect IP67 devices based on the 7/8" standard connectors also called Mini-Change®.


Ordering Information

Brad® Mini-Change® Single-Ended 5 Pole Cordsets





5 Pole Mini-Change® Auxiliary Power PUR Cable				
	Male Straight		Female Straight	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	105006B21M020	130006-8194	105000B21M020	130006-8151
5m	105006B21M050	130006-8139	105000B21M050	130006-8131
10m	105006B21M100	130006-8140	105000B21M100	130006-8132
20m	105006B21M200	130006-8141	105000B21M200	130006-8133
30m	105006B21M300	130006-8142	105000B21M300	130006-8134

Brad® Mini-Change® Double-Ended 5 Pole Cordsets



5 Pole Mini-Change® Auxiliary Power PUR Cable				
	Female to Male Straight		Female to Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	115030B21M010	130010-8029	115033B21M010	130010-8036
2m	115030B21M020	130010-8030	115033B21M020	130010-8037
3m	115030B21M030	130010-8031	115033B21M030	130010-8038
5m	115030B21M050	130010-8032	115033B21M050	130010-8039
10m	115030B21M100	130010-8033	115033B21M100	130010-8040
15m	115030B21M150	130010-8034	115033B21M150	130010-8041
20m	115030B21M200	130010-8035	115033B21M200	130010-8042

Brad® Mini-Change® 5 Pole Receptacles



5 Pole Mini-Change® Auxiliary Power PUR Cable				
	Male Receptacle		Female Receptacle	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	1R5006A80M010	130013-8078	1R5000A80M010	130013-8076
2m	1R5006A80M020	130013-8079	1R5000A80M020	130013-8077

Description	Engineering No.	Standard Order No.
Gasket for Receptacle, 1/2"	00-5087	130180-0059
Locknut for Receptacle, 1/2" 14NPT	30-1100	130184-0031

Brad® Mini-Change® 7/8" Auxiliary Power Infrastructure Components



Mini-Change® 5 Pole Power Cable Specification

5 Pole 16 AWG cable for 24V power distribution

Conductors: 5 x 16 AWG (1.5mm²)
Black, Blue, Green/Yellow, Brown, White

Jacket Material: Grey PUR, halogen free, flame retardant, oil resistant

Voltage Rating: 300V


Operating Temperature: -40°C to +80°C

C-Track and Torsion Flex Rated (>2Mio Cycles)

Bend radius: 10x cable diameter

Approvals: UL

Mini-Change® 5 Pole Female Connector Pinout (Front view)




1. Black – Output Power V-
2. Blue – Bus Power V-
3. Green/Yellow – Ground
4. Brown – Bus Power V+
5. White – Output Power V+



Ordering Information


Brad® Mini-Change® 5 Pole Field Attachable Connector




Male		Female	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1A5006-34	130017-0029	1A5000-34	130017-0023

Brad® Mini-Change® 5 Pole Tees


Mini-Change® Tee	
Engineering No.	Standard Order No.
DN3020	130035-0057




Mini-Change® Y-Splitter	
Engineering No.	Standard Order No.
DN3200	130035-0071



Mini-Change® Tee w/M12 Drop	
Engineering No.	Standard Order No.
DND3020	130039-0341




Mini-Change® Distribution Box		
Description	Engineering No.	Standard Order No.
4 Ports	DN4000	130036-0005
6 Ports	DN6000	130036-0008




Brad® Mini-Change® Accessories

Mini-Change® Caps		
Description	Engineering No.	Standard Order No.
Int. Thread	65-0086	130201-1111
Ext. Thread	65-0085	130201-1109



Brad® Mini-Change® 7/8" Auxiliary Power Infrastructure Components



Note:
Further technical information, datasheet or drawing can be downloaded from the Molex® website using the Standard Order part number listed.

Plug & Play 5 Pole power distribution infrastructure to interconnect IP67 devices based on the A-Code M12 standard connectors.

Ordering Information

Brad® Micro-Change® M12 Single-Ended 5 Pole Cordsets



B42 WSOR Cable				
	Male Straight		Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	805006B42M020	120065-2280	805007B42M020	120065-2292
5m	805006B42M050	120065-2281	805007B42M050	120065-2293
10m	805006B42M100	120065-2282	805007B42M100	120065-2294
20m	805006B42M200	120065-9546	805007B42M200	120065-9545
30m	805006B42M300	120065-9547	—	—



B42 WSOR Cable				
	Female Straight		Female 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	805000B42M020	120065-2256	805001B42M020	120065-2268
5m	805000B42M050	120065-2257	805001B42M050	120065-2269
10m	805000B42M100	120065-2258	805001B42M100	120065-2270
20m	805000B42M200	120065-9543	805001B42M200	120065-9542
30m	805000B42M300	120065-9544	—	—

Brad® Micro-Change® M12 Auxiliary Power 5 Pole Receptacles



PVC Wires				
	Male		Female	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
2m	8R5E36E03M020	120070-8173	8R5E30E03M020	120070-8171
3m	8R5E36E03M030	120070-8174	8R5E30E03M030	120070-8172

Brad® Micro-Change® M12 Auxiliary Power Infrastructure Components



B42 PUR WSOR cable Specification*

Conductors: 5x0,34 mm²

(Brown, White, Blue, Black, Green/Yellow)

Jacket material: Black Blend PUR, flame retardant, oil, UV & Weld Slag resistant, silicone & FCKW free

Diameter 5 Pole: 5,5 ±0,2mm

Voltage Rating: 600V, max 4 Amps

Static Operating Temp: -40 to +90°C

Dynamic Operating Temp: -25 to +80°C

Drag Chain (>5 Mio Cycles) & torsion suitable

Approvals: UL, CSA

B42 PUR WSOR 200m

Engineering No.	Standard Order No.
B42-5-200	112180-0064

* Detailed cable specification attached to bulk cable drawings

Ordering Information

Brad® Micro-Change® M12 Auxiliary Power Double-Ended 5 Pole Cordsets



B42 WSOR Cable				
	Female to Male Straight		Female to Male 90°	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
1m	885030B42M010	120066-8824	885033B42M010	120066-8955
2m	885030B42M020	120066-8825	885033B42M020	120066-8956
3m	885030B42M030	120066-8826	885033B42M030	120066-8957
5m	885030B42M050	120066-8827	885033B42M050	120066-8958
10m	885030B42M100	120066-8828	885033B42M100	120066-8959
15m	885030B42M150	120065-9548	—	—
20m	885030B42M200	120065-9549	—	—

Brad® Micro-Change® M12 5 Pole Field Attachable



	Male		Female	
Max. Wire Size	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3.3-6.6	8A5006-31	120071-0045	8A5000-31	120071-0041
4.1-8.1	8A5006-32	120071-0047	8A5000-32	120071-0043

Brad® Micro-Change® M12 5 Pole Accessories




5 Poles M12 Y-Splitter	
Engineering No.	Standard Order No.
0812-05EFJ-0000A	120068-5107

5 Poles M12 Tee	
Engineering No.	Standard Order No.
0812-051FJ-00000	120068-8009

Brad® Micro-Change® M12 Auxiliary Power Infrastructure Components




Micro-Change® A-Code M12 5 Pole Auxiliary Power Connector on the IO modules.
Female Pinout
(Front view):



- 1. Brown – Module Power V+
- 2. White – Output Power V+
- 3. Blue – Ground
- 4. Black – Ground
- 5. Green/Yellow – Protective Earth

Micro-Change® M12 5 Pole Tee and Y-Splitter Wiring




IP67 rated passive IO module for harsh environments are designed to concentrate the sensor/actuator signals into one unique home run cable for a better mechanical infrastructure wiring on the machine.

Specifications

IP67 Molded PBT Housing, color Black
Single or Dual Input/Output signal per port
Indicating LED for Power and sensor trigger
PNP Version (available also in NPN version)
Electrical: 10-30V DC max. & 12.0A max. (4.0A max. per port)
Approvals: UL, CSA, IP67, NEMA 6



Ordering Information

Brad® M12 Distribution Boxes with PUR Home Run Cable





		4 Ports		8 Ports	
IO Type	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
Single IO	5m	BTB400P-FBW-05	120248-0004	BTB800P-FBW-05	120248-0022
	10m	BTB400P-FBW-10	120248-0005	BTB800P-FBW-10	120248-0023
Dual IO	5m	BTB405P-FBW-05	120248-0031	BTB805P-FBW-05	120248-0049
	10m	BTB405P-FBW-10	120248-0032	BTB805P-FBW-10	120248-0050

Brad® M12 Distribution Boxes with Field Attachable Terminals



	4 Ports		8 Ports	
IO Type	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
Dual IO	BTB403P-FBA	120248-0085	BTB803P-FBA	120248-0087

Brad® M12 Distribution Boxes with M23 Connector and Home Run Cable



8 Ports		
IO Type	Engineering No.	Standard Order No.
Single IO	BTB801P-FBC	120248-0060
Dual IO	BTB803P-FBC	120248-0066


Single IO Home Run Cable (12p/11 wires)			Dual IO Home Run Cable (19p/19 wires)	
Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
10m	K02101B80M100*	120094-8150	K03001B80M100*	120094-8163

*Home run cable also available in 1m, 5m, 15m, 20m, 30m and also with m23 straight connector.


**Brad®
Sensor/Actuator
Distribution Boxes**



Micro-Change® M12 Single IO Connector Wiring



Micro-Change® M12 Dual IO Connector Wiring



Ordering Information

Brad® M8 Distribution Boxes with Side Mount PUR Home Run Cable




		4 Ports		6 Ports	
IO Type	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
Single IO	5m	BEB401P-FBW-05	120247-0001	BEB601P-FBW-05	120247-0040
	10m	BEB401P-FBW-10	120247-0002	BEB601P-FBW-10	120247-0041




		8 Ports		10 Ports	
IO Type	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
Single IO	5m	BEB801P-FBW-05	120247-0012	BEBA01P-FBW-05	120247-0006
	10m	BEB801P-FBW-10	120247-0013	BEBA01P-FBW-10	120247-0007

Brad® M8 Distribution Boxes with M16 Connector and Home Run Cable



	Single IO Distribution Box with M16 connector	
Ports	Engineering No.	Standard Order No.
4	BNB401P-FBC	120247-0059
6	BNB601P-FBC	120247-0061
8	BNB801P-FBC	120247-0063
10	BNBA01P-FBC	120247-0065




	M16 Single IO Home Run Cable 10 Meter	
Block	Engineering No.	Standard Order No.
4 Ports	L04301B78M100*	130023-8011
6 Ports	L04201B78M100*	130023-8017
8 Ports	L04101B78M100*	130023-8023
10 Ports	L04A01B78M100*	130023-8029

*Home run cable also available in 5m and 15m length.

Brad® Sensor/Actuator Distribution Boxes



Nano-Change® M8 Single IO Connector Wiring



Note:
Further technical information, datasheet or drawing can be downloaded from the Molex® website using the ordering part number.

Brad® Micro-Change® M12 connectivity is a ready-to-use solution based on the A-Code M12 standard with IP67/68 rating to wire a wide range of sensors and actuators from proximity switches to rotary encoders in harsh environments.

Brad® Micro-Change® M12 Sensor/Actuator Connectivity



Ordering Information

Brad® Micro-Change® M12 Single-Ended Cordsets



B30 WSOR Cable									
		Female Straight		Female 90°		Male Straight		Male 90°	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	1m	803000B30M010	120065-2247	803001B30M010	120065-2259	803006B30M010	120065-2271	803007B30M010	120065-2283
	2m	803000B30M020	120065-2248	803001B30M020	120065-2260	803006B30M020	120065-2272	803007B30M020	120065-2284
	5m	803000B30M050	120065-2249	803001B30M050	120065-2261	803006B30M050	120065-2273	803007B30M050	120065-2285
	10m	803000B30M100	120065-2250	803001B30M100	120065-2262	803006B30M100	120065-2274	803007B30M100	120065-2286
4	1m	804000B30M010	120065-2251	804001B30M010	120065-2263	804006B30M010	120065-2275	804007B30M010	120065-2287
	2m	804000B30M020	120065-2252	804001B30M020	120065-2264	804006B30M020	120065-2276	804007B30M020	120065-2288
	5m	804000B30M050	120065-2253	804001B30M050	120065-2265	804006B30M050	120065-2277	804007B30M050	120065-2289
	10m	804000B30M100	120065-2254	804001B30M100	120065-2266	804006B30M100	120065-2278	804007B30M100	120065-2290
5	1m	805000B30M010	120065-9518	805001B30M010	120065-9522	805006B30M010	120065-9526	805007B30M010	120065-9530
	2m	805000B30M020	120065-9519	805001B30M020	120065-9523	805006B30M020	120065-9527	805007B30M020	120065-9531
	5m	805000B30M050	120065-9520	805001B30M050	120065-9524	805006B30M050	120065-9528	805007B30M050	120065-9532
	10m	805000B30M100	120065-9521	805001B30M100	120065-9525	805006B30M100	120065-9529	805007B30M100	120065-9533
8	1m	808000B41M010	120065-2306	808001B41M010	120065-2310	808006B41M010	120065-2302	808007B41M010	120065-2314
	2m	808000B41M020	120065-9458	808001B41M020	120065-2311	808006B41M020	120065-9453	808007B41M020	120065-2315
	5m	808000B41M050	120065-2308	808001B41M050	120065-2312	808006B41M050	120065-2304	808007B41M050	120065-2316
	10m	808000B41M100	120065-9463	808001B41M100	120065-2313	808006B41M100	120065-2305	808007B41M100	120065-2317

Build-A-Part Number Configuration Code

	Cable	Code
0.34mm ²	PVC	E03
	WSOR	B30
	PUR	H09
0.25mm ²	PVC	E02
	WSOR	B41
	PUR	H08

803000B30M020H

← ID Tag Option

↑ Cable Length M020 for 2m

Ordering Information

Brad® Micro-Change® M12 Double-Ended Cordsets



B30 WSOR Cable					
		Fem. To Male Straight		Fem. 90° To Male Straight	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	0.6m	883030B30M006	120066-8889	883031B30M006	120066-8877
	1m	883030B30M010	120066-8890	883031B30M010	120066-8878
	2m	883030B30M020	120066-8891	883031B30M020	120066-8879
	3m	883030B30M030	120066-8892	883031B30M030	120066-8880
	5m	883030B30M050	120066-8893	883031B30M050	120066-8881
	10m	883030B30M100	120066-8894	883031B30M100	120066-8882
4	0.6m	884030B30M006	120066-8817	884031B30M006	120066-8829
	1m	884030B30M010	120066-8818	884031B30M010	120066-8830
	2m	884030B30M020	120066-8819	884031B30M020	120066-8831
	3m	884030B30M030	120066-8820	884031B30M030	120066-8832
	5m	884030B30M050	120066-8821	884031B30M050	120066-8833
	10m	884030B30M100	120066-8822	884031B30M100	120066-8834
5	0.6m	885030B30M006	120066-8991	885031B30M006	120066-8997
	1m	885030B30M010	120066-8992	885031B30M010	120066-8998
	2m	885030B30M020	120066-8993	885031B30M020	120066-8999
	3m	885030B30M030	120066-8994	885031B30M030	120066-9000
	5m	885030B30M050	120066-8995	885031B30M050	120066-9001
	10m	885030B30M100	120066-8996	885031B30M100	120066-9002
8	0.6m	888030B41M006	120066-8895	888031B41M006	120066-8883
	1m	888030B41M010	120066-8896	888031B41M010	120066-8884
	2m	888030B41M020	120066-8897	888031B41M020	120066-8885
	3m	888030B41M030	120066-8898	888031B41M030	120066-8886
	5m	888030B41M050	120066-8899	888031B41M050	120066-8887
	10m	888030B41M100	120066-8900	888031B41M100	120066-8888

Brad® Micro-Change® M12 Front Mount Receptacles



Wires with PVC Jacket					
		Male		Female	
Poles	Mount Thread	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	PG9	8R4J36E03C3003	120070-0156	8R4J30E03C3003	120070-0395
	M14x1	8R4E36E03C3003	120011-0017	8R4E30E03C3003	120011-0013
5	PG9	8R5J36E03C3003	120070-0231	8R5J30E03C3003	120070-0229
	M14x1	8R5E36E03C3003	120011-0035	8R5E30E03C3003	120011-0033

Brad® Micro-Change® M12 Sensor/Actuator Connectivity



B30 PUR WSOR Cable Specification*

Conductors: 3x0,34 mm², 4x0,34 mm² or 5x0,34 mm² **

(Brown, White, Blue, Black, Grey)

Jacket material: Black Blend PUR, flame retardant, oil, UV & Weld Slag resistant, silicone & FCKW free

Diameter 3 Pole: 4,8 + -0,2mm

Diameter 4 Pole: 5,1 + -0,2mm

Diameter 5 Pole: 5,5 + -0,2mm

Voltage Rating: 600V, max 4 Amps

Static Operating Temp: -40 to +90°C

Dynamic Operating Temp: -25 to +80°C

Drag Chain (>5 Mio Cycles) & torsion suitable

Approvals: UL, CSA

B30 PUR WSOR 200m Bulk Cable

Engineering No.	Standard Order No.
B30-3-200	112180-0003
B30-4-200	112180-0004
B30-5-200	112180-0005

* Detailed cable specification attached to bulk cable drawings

** 8 pole cable specification: see B41 description in M8 section

Ordering Information

Brad® Micro-Change M12

Single-Ended Cordsets with LED Wiring



B30 WSOR Cable					
		Female Straight		Female 90°	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	1m	8030P0B30M010	120067-8454	8030P1B30M010	120067-8450
	2m	8030P0B30M020	120067-8455	8030P1B30M020	120067-8451
	3m	8030P0B30M030	120067-8456	8030P1B30M030	120067-8452
	5m	8030P0B30M050	120067-8431	8030P1B30M050	120067-8432
	10m	8030P0B30M100	120067-8457	8030P1B30M100	120067-8453
4	1m	8040P0B30M010	120067-8463	8040P1B30M010	120067-8458
	2m	8040P0B30M020	120067-8464	8040P1B30M020	120067-8459
	3m	8040P0B30M030	120067-8465	8040P1B30M030	120067-8460
	5m	8040P0B30M050	120067-8430	8040P1B30M050	120067-8461
	10m	8040P0B30M100	120067-8466	8040P1B30M100	120067-8462

Brad® Micro-Change M12

Double-Ended Cordsets with LED Wiring





B30 WSOR Cable					
		Female to Male Straight		Female 90° to Male Straight	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	1m	8830P6B30M010	120067-8472	8830P7B30M010	120067-8467
	2m	8830P6B30M020	120067-8473	8830P7B30M020	120067-8468
	3m	8830P6B30M030	120067-8474	8830P7B30M030	120067-8469
	5m	8830P6B30M050	120067-8475	8830P7B30M050	120067-8470
	10m	8830P6B30M100	120067-8476	8830P7B30M100	120067-8471
4	1m	8840P6B30M010	120067-8423	8840P7B30M010	120067-8420
	2m	8840P6B30M020	120067-8424	8840P7B30M020	120067-8421
	3m	8840P6B30M030	120067-8478	8840P7B30M030	120067-8477
	5m	8840P6B30M050	120067-8425	8840P7B30M050	120067-8422
	10m	8840P6B30M100	120067-8426	8840P7B30M100	120067-8427

Brad® Micro-Change M12 with LED



Micro-Change M12 with LED Wiring



Ordering Information

Brad® M12 Single-Ended Shielded Cable



BS1 WSOR Shielded Cable					
		Female Straight		Female 90°	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	1m	804S00BS1M010	120069-8595	804S01BS1M010	120069-8606
	2m	804S00BS1M020	120069-8596	804S01BS1M020	120069-8485
	3m	804S00BS1M030	120069-8725	804S01BS1M030	120069-8724
	5m	804S00BS1M050	120069-8487	804S01BS1M050	120069-8486
	10m	804S00BS1M100	120069-8556	804S01BS1M100	120069-8559
5	1m	805S00BS1M010	120069-8597	805S01BS1M010	120069-8607
	2m	805S00BS1M020	120069-8598	805S01BS1M020	120069-8608
	3m	805S00BS1M030	120069-8727	805S01BS1M030	120069-8726
	5m	805S00BS1M050	120069-8538	805S01BS1M050	120069-8542
	10m	805S00BS1M100	120069-8539	805S01BS1M100	120069-8543

Brad® M12 Double-Ended Shielded Cable



BS1 WSOR Shielded Cable					
		Female to Male Straight		Female 90° to Male Straight	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	1m	884S30BS1M010	120069-8649	884S31BS1M010	120069-8689
	2m	884S30BS1M020	120069-8650	884S31BS1M020	120069-8690
	3m	884S30BS1M030	120069-8651	884S31BS1M030	120069-8691
	5m	884S30BS1M050	120069-8652	884S31BS1M050	120069-8692
	10m	884S30BS1M100	120069-8653	884S31BS1M100	120069-8693
5	1m	885S30BS1M010	120069-8654	885S31BS1M010	120069-8694
	2m	885S30BS1M020	120069-8655	885S31BS1M020	120069-8695
	3m	885S30BS1M030	120069-8656	885S31BS1M030	120069-8696
	5m	885S30BS1M050	120069-8657	885S31BS1M050	120069-8697
	10m	885S30BS1M100	120069-8658	885S31BS1M100	120069-8698

BS1 Shielded WSOR Cable Specification*

Conductors: 4x0,34 mm² or
5x0,34 mm²

(Brown, White, Blue, Black, Grey)

Jacket material: Black Blend PUR,
flame retardant, oil, UV & Weld
Slag resistant, silicone & FCKW
free

Braid coverage > 80%

Diameter 4 Pole: 5,7 + -0,2mm

Diameter 5 Pole: 6,1 + -0,2mm

Voltage Rating: 600V, max 4
Amps

Static Operating Temp: -40 to
+90°C

Dynamic Operating Temp: -25 to
+80°C

Drag Chain (>5 Mio Cycles) &
torsion suitable


Approvals: UL, CSA

Ordering Information
Brad® M12 Cable Splitters




B30 WSOR Cable					
		2x Female to Male Straight		2x Female 90° to Male Straight	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	.6m	884A30B30M006	120068-8193	884A31B30M006	120068-8189
	1m	884A30B30M010	120068-8194	884A31B30M010	120068-8190
	2m	884A30B30M020	120068-8195	884A31B30M020	120068-8191
	5m	884A30B30M050	120068-8196	884A31B30M050	120068-8192

Brad® Micro-Change®
M12 Y-Splitters &
Adapters



Y-Splitter M12 to M12		
1x M12 Male to 2x M12 Female		
Poles	Engineering No.	Standard Order No.
4	081204EMF00000	120068-0294
5	081205EMF00000	120068-0139



Y-Splitter M12 to M8		
1x M12 Male to 2x M8 Female		
Poles	Engineering No.	Standard Order No.
4	080804EMF00000	120089-0031




Adapter Connector		
1xM12 Male to 1xM8 Female		
Poles	Engineering No.	Standard Order No.
3	483030	120033-0002
4	484030	120033-0001


Brad®
Micro-Change® M12
Sensor/Actuator
Connectivity



M12 Cable Splitter Wiring



Y-Splitter
Wiring Schematic




Ordering Information

Brad® Micro-Change® M12 Field Attachable Connectors



		Male Straight		Male 90°	
Poles	Max. Wire Size	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	3.3-6.6	8A4006-31	120071-0038	8A4007-31	120071-0040
	4.1-8.1	8A4006-32	120071-0039	8A4007-32	120071-5011
5	3.3-6.6	8A5006-31	120071-0045	8A5007-31	120071-0049
	4.1-8.1	8A5006-32	120071-0047	8A5007-32	120071-0071



		Female Straight		Female 90°	
Poles	Max. Wire Size	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
4	3.3-6.6	8A4000-31	120071-0035	8A4001-31	120071-0037
	4.1-8.1	8A4000-32	120071-0036	8A4001-32	120071-5010
5	3.3-6.6	8A5000-31	120071-0041	8A5001-31	120071-0044
	4.1-8.1	8A5000-32	120071-0043	8A5001-32	120071-0070

Brad® Micro-Change® M12 Closure Caps



Plastic Closure Cap

To Cover Male		To Cover Female	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
—	120308-0680	—	120358-0030



Rubber Closure Cap with Leash


To Cover Male		To Cover Female	
Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
—	120076-5046	—	120076-5047

Brad® Micro-Change® M12 Sensor/Actuator Connectivity




Micro-Change® M12 Connector Pinout

3 Pole




1 - Brown 4 - Black
3 - Blue

4 Pole




1 - Brown 3 - Blue
2 - White 4 - Black

5 Pole



1 - Brown 4 - Black
2 - White 5 - Grey
3 - Blue

8 Pole



1 - White 5 - Grey
2 - Brown 6 - Pink
3 - Green 7 - Blue
4 - Yellow 8 - Red



Brad® Nano-Change® M8 connectivity provides a rugged and space-saving solution to wire a wide range of sensors and actuators from proximity switches to rotary encoders in harsh environments.

Brad® Nano-Change® M8 Sensor/Actuator Connectivity



Ordering Information

Brad® Nano-Change® M8 Single-Ended Cordsets



B41 WSOR Cable									
		Female Straight		Female 90°		Male Straight		Male 90°	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	1m	403000B41M010	120086-8655	403001B41M010	120086-8667	403006B41M010	120086-8631	403007B41M010	120086-8643
	2m	403000B41M020	120086-8656	403001B41M020	120086-8668	403006B41M020	120086-8632	403007B41M020	120086-8644
	5m	403000B41M050	120086-8657	403001B41M050	120086-8669	403006B41M050	120086-8633	403007B41M050	120086-8645
	10m	403000B41M100	120086-8658	403001B41M100	120086-8670	403006B41M100	120086-8634	403007B41M100	120086-8646
4	1m	404000B41M010	120086-8659	404001B41M010	120086-8671	404006B41M010	120086-8635	404007B41M010	120086-8647
	2m	404000B41M020	120086-8660	404001B41M020	120086-8672	404006B41M020	120086-8636	404007B41M020	120086-8648
	5m	404000B41M050	120086-8661	404001B41M050	120086-8673	404006B41M050	120086-8637	404007B41M050	120086-8649
	10m	404000B41M100	120086-8662	404001B41M100	120086-8674	404006B41M100	120086-8638	404007B41M100	120086-8650
5	1m	405000B41M010	120086-8663	405001B41M010	120086-8675	405006B41M010	120086-8639	405007B41M010	120086-8651
	2m	405000B41M020	120086-8664	405001B41M020	120086-8676	405006B41M020	120086-8640	405007B41M020	120086-8652
	5m	405000B41M050	120086-8665	405001B41M050	120086-8677	405006B41M050	120086-8641	405007B41M050	120086-8653
	10m	405000B41M100	120086-8666	405001B41M100	120086-8678	405006B41M100	120086-8642	405007B41M100	120086-8654

Build-A-Part Number Configuration Code

	Cable	Code
0.34mm²	PVC	E03
	WSOR	B30
	PUR	H09
0.25mm²	PVC	E02
	WSOR	B41
	PUR	H08

403000B41M020H

← ID Tag Option

↑ Cable Length M020 for 2m

Ordering Information

Brad® Nano-Change® M8 Double-Ended Cordsets



Brad® Nano-Change® M8 Sensor/Actuator Connectivity



B41 WSOR Cable					
		Female to Male Straight		Fem. 90° to Male Straight	
Poles	Length	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	.6m	443030B41M006	120087-8703	443031B41M006	120087-8721
	1m	443030B41M010	120087-8704	443031B41M010	120087-8722
	2m	443030B41M020	120087-8705	443031B41M020	120087-8723
	3m	443030B41M030	120087-8706	443031B41M030	120087-8724
	5m	443030B41M050	120087-8707	443031B41M050	120087-8725
4	.6m	444030B41M006	120087-8709	444031B41M006	120087-8727
	1m	444030B41M010	120087-8710	444031B41M010	120087-8728
	2m	444030B41M020	120087-8711	444031B41M020	120087-8729
	3m	444030B41M030	120087-8712	444031B41M030	120087-8730
	5m	444030B41M050	120087-8713	444031B41M050	120087-8731
5	.6m	445030B41M006	120087-8715	445031B41M006	120087-8733
	1m	445030B41M010	120087-8716	445031B41M010	120087-8734
	2m	445030B41M020	120087-8717	445031B41M020	120087-8735
	3m	445030B41M030	120087-8718	445031B41M030	120087-8736
	5m	445030B41M050	120087-8719	445031B41M050	120087-8737

Brad® Nano-Change® M8 Receptacles



		Male		Female	
Poles	Mount Thread	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	M8x0.5 Front	4R3F06E02C3003	120031-0004	4R3F30E02C3003	120031-0015
	M8x1 Back	4R3F46E02C200	120090-5073	4R3L40E02C200	120090-5104
4	M8x0.5 Front	4R4F06E02C3003	120031-0006	4R4F30E02C3003	120031-0049
	M8x1 Back	4R4F46E02C200	120090-5078	4R4L40E02C200	120090-8037
5	M8x0.5 Front	4R5F06E02C3003	120031-0027	4R5F46E02C200	120031-0028
	M8x1 Back	4R5F30E02C3003	120031-0028	4R5L40E02C200	120090-8056

B41 WSOR Cable Specification*

Conductors: 3x0,25 mm², 4x0,25 mm², 5x0,25 mm², 8x0,25 mm²
(Brown, White, Blue, Black, Grey)
(BN, WH, BE, RD, GY, GN, YE, PK)

Jacket material: Black Blend PUR, flame retardant, oil, UV & Weld Slag resistant, silicone & FCKW free

Diameter 3 Pole: 4,5 +-0,2mm

Diameter 4 Pole: 4,8 +-0,2mm

Diameter 5 Pole: 5,3 +-0,2mm

Diameter 8 Pole: 6,4 +-0,2mm

Voltage Rating: 600V, max 4 Amps

Static Operating Temp: -40 to +90°C

Dynamic Operating Temp: -25 to +80°C

Drag Chain (>5 Mio Cycles) & torsion suitable

Approvals: UL, CSA

B41 WSOR Bulk cable

Engineering No.	Standard Order No.
B41-3-200	112180-0067
B41-4-200	112180-0068
B41-5-200	112180-0069
B41-8-100	112180-0006

* Detailed cable specification attached to bulk cable drawings

Brad®
Nano-Change® M8
Sensor/Actuator
Connectivity

Ordering Information

Brad® Nano-Change® M8 Single-Ended Cordsets w/LED



		Female 90°	
Poles	Length	Engineering No.	Standard Order No.
3	1m	4030P1B41M010	120086-8687
	2m	4030P1B41M020	120086-8688
	5m	4030P1B41M050	120086-8689
	10m	4030P1B41M100	120086-8690




Brad® Nano-Change® M8 Double-Ended Cordsets w/LED




		Female 90° to Male Straight	
Poles	Length	Engineering No.	Standard Order No.
3	1m	4430P7B41M006	120087-8779
	2m	4430P7B41M010	120087-8780
	5m	4430P7B41M020	120087-8781
	10m	4430P7B41M050	120087-8782

Nano-Change® M8 LED
Connector Wiring



Brad® Nano-Change® M8 Y-Splitters & Adapters

Y-Splitter		
1x M8 Male to 2x M8 Female		
Poles	Engineering No.	Standard Order No.
4	080804LMF00000	120089-0033




Adapter Connector		
1x M8 Male to 1x M12 Female		
Poles	Engineering No.	Standard Order No.
3	853030	120017-0004
4	854030	120017-0003



Y-Splitter Wiring Schematic

M8 to M8 4 Pole



Note:
M8 male connector thread is fixed.

Ordering Information
Brad® Nano-Change® M8
Field Attachable Connectors




		Male Straight		Male 90°	
Poles	Max Wire Size	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	3.5-5mm	N03MA03124	120091-0004	N03MA04124	120091-0006
4	3.5-5mm	N04MA03124	120091-0010	N04MA04124	120091-0012



		Female Straight		Female 90°	
Poles	Max Wire Size	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
3	3.5-5mm	N03FA03124	120091-0001	N03FA04124	120091-0003
4	3.5-5mm	N04FA03124	120091-0007	N04FA04124	120091-0009

Brad® Nano-Change® M8 Closure Caps



Plastic Closure Cap


To Cover Female	
Engineering No.	Standard Order No.
—	120308-0677

Brad®
Nano-Change® M8
Sensor/Actuator
Connectivity




Nano-Change® M8
Connector Pinout
(front view)

3 Pole




1 - Brown 4 - Black
3 - Blue

4 Pole



1 - Brown 3 - Blue
2 - White 4 - Black

5 Pole




1 - Brown 4 - Black
2 - White 5 - Grey
3 - Blue



The mPm® DIN valve connectors conform to the industry standard of electrical connectors EN 175301-803, which are commonly used with solenoid valves. The new generation of Molex® DIN connectors provides unsurpassed sealing performance, easier assembly and mounting and lower applied costs.

Ordering Information


Brad® mPm® Field Attachable DIN Valve Connectors



Form A External Thread		
Description	Engineering No.	Standard Order No.
Non-Electronic	C28200N2RSN	121201-0034
With Electronic	S28200TC422RSN	121207-0358




Form B External Thread		
Description	Engineering No.	Standard Order No.
Non-Electronic	C22200N2RSN	121202-0012
With Electronic	S22200TC422RSN	121208-0230



Form C External Thread		
Description	Engineering No.	Standard Order No.
Non-Electronic	C92200N2TSN	121203-0009
With Electronic	S92200TC422TSN	121209-0197



Form Micro External Thread		
Description	Engineering No.	Standard Order No.
Non-Electronic	C25200N2TSN	121204-0010
With Electronic	S25200TC422TSN	121210-0332



Form Industrial External Thread		
Description	Engineering No.	Standard Order No.
Non-Electronic	C29200N2TSN	121205-0012
With Electronic	S29200TC422TSN	121211-0332

Brad® mPm® DIN Valve Connectors



Circuit C4 Schematics


Bipolar yellow LED and VDR to protect supply and switch.

Available voltage rating on C4 circuit:

12, 24, 48, 115 and 230 V AC-DC

12, 24 and 115V AC-DC

(for type 192 only)



Note:




The mPm® DIN valve connectors are available in various version, Pole count, housing and electronics. For further information consult our website or automation catalog or your local sales support.

Further technical information, datasheet or drawing can be downloaded from the Molex® website using the ordering part number.


The mPm® connectors with molded-in cable are suitable for use with most types of solenoid. They offer a fast and efficient method of connection resulting in greatly reduced installation time and costs.

Ordering Information

Brad® mPm® DIN Valve Connectors Over Molded to M12 Male Connector




DIN Valve Connector, FORM A, C4 Circuit, Ground Pos H6/H12				
Length	Male Straight		Male 90°	
	Engineering No.	Standard Order No.	Engineering No.	Standard Order No.
.6m	E850B0P12M006	121036-0192	E850B2P12M006	121036-0208
1m	E850B0P12M010	121036-0193	E850B2P12M010	121036-0209
1.5m	E850B0P12M015	121036-0194	E850B2P12M015	121036-0821
3m	E850B0P12M030	121036-0356	E850B2P12M030	121036-0211




DIN Valve Connector, FORM Industrial, C4 Circuit, Ground Pos H6				
.6m	F850B0P12M006	121036-0352	F850B2P12M006	121036-0505
1m	F850B0P12M010	121036-0255	F850B2P12M010	121036-0506
1.5m	F850B0P12M015	121036-0822	F850B2P12M015	121036-0823
3m	F850B0P12M030	121036-0257	F850B2P12M030	121036-0824



DIN Valve Connector, FORM B, C4 Circuit, Ground Pos H6				
.6m	D850B0P12M006	121036-0056	D850B2P12M006	121036-0828
1m	D850B0P12M010	121036-0825	D850B2P12M010	121036-0829
1.5m	D850B0P12M015	121036-0826	D850B2P12M015	121036-0830
3m	D850B0P12M030	121036-0827	D850B2P12M030	121036-0831



DIN Valve Connector, FORM C, C4 Circuit, Ground Pos H6/H12				
.6m	H850B0P12M006	121036-0295	H850B2P12M006	121036-0832
1m	H850B0P12M010	121036-0296	H850B2P12M010	121036-0305
1.5m	H850B0P12M015	121036-0471	H850B2P12M015	121036-0833
3m	H850B0P12M030	121036-0440	H850B2P12M030	121036-0834



DIN Valve Connector, FORM Micro, C4 Circuit, Ground Pos H6/H12				
.6m	G850B0P12M006	121036-0406	G850B2P12M006	121036-0836
1m	G850B0P12M010	121036-0277	G850B2P12M010	121036-0621
1.5m	G850B0P12M015	121036-0835	G850B2P12M015	121036-0837
3m	G850B0P12M030	121036-0481	G850B2P12M030	121035-0270

Brad® mPm® DIN Valve Connectors



DIN PUR/PVC Cable Specification

Conductors: 3x0,5mm² PVC
(Brown, Blue, Green/Yellow)

Jacket Material: Black PUR

Voltage Rating: 300V

Operating Temperature:
-5 to +90°C (flexing)

-30 to +90°C (static)

Diameter: 5,5 ±0,3 mm

Note:

The mPm® DIN valve over molded cordsets are available in various versions, Pole count, housing, cable, lengths and electronics. For further information consult our website or automation catalog or your local sales support.

Further technical information, datasheet or drawing can be downloaded from the Molex® website using the ordering part number.

Get more insights at: molex.com/industry/industrial.html